Ref: HSD/D3

Safety Data Sheet

according to 1907/2006/EC Issue No: 8 D Date of Issue: 24th October, 2011

1. Product and Company Identification

Product Name:	D-BAF	2	
Intended Uses:	Bitume	Bitumen solution dowel bar debonding compound.	
Manufacturer:	Kingst	UNIVERSAL SEALANTS (UK) LIMITED Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear. NE38 8QA, United Kingdom	
Tel: +44 (0) 191 416 1530		Fax: +44 (0) 191 415 4377	Email: info@usluk.com
24 Hour Emergency Tel:		CHEMTREC +1 703 527 3887	

2. Hazard Identification

Possible Hazards:

R10:	Flammable.
R51/53:	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
R65:	Harmful: may cause lung damage if swallowed.

3. Composition / Information on Ingredients

Name Petroleum	CAS No	EINECS	Conc. (w/w)	Classification	R. Phrases
Solvent	N/A	N/A	<50%	F	10
NOTE: Benzene (CAS No. 71-43-2) will normally be present in trace amounts but will always be less					
than 0.1% w/w marker level in the 21 st ATP to the Dangerous Substances Directive. This product is NOT CLASSIFIED as a carcinogen under the CHIP3 regulations.					

4. First Aid Measures

Inhalation:		or sickness remove to fresh air, keep patient warm and turn to the recovery position. Seek medical assistance.	
Skin Contact:	Promptly remove contaminated clothing and wash the affected area with plenty of soap and water to ensure all traces of product are removed, then rinse thoroughly. Any contaminated clothing must be thoroughly cleaned before re-using. Seek medical advice if irritation persists.		
Eye Contact:	Flush with copious amounts of clean water for at least 15 minutes, with the eye lids held open. Seek medical attention.		
Ingestion:	Wash out mouth with water. Keep patient at rest and obtain medical attention. DO NOT INDUCE VOMITING.		
5. Fire Fighting	g Measures		
Suitable Exting	guisher Media:	Alcohol-resistant foam, dry powder, carbon dioxide or sand.	
Unsuitable Extinguishing Media:		Water jet.	
Exposure Haza	ards:	May give off toxic fumes if heated or involved in a fire, including carbon monoxide, carbon dioxide.	

s	Safety Data Sheet
	rding to 1907/2006/EC Issue No: 8 Date of Issue: 24 th October, 2011
Special Protective Equipment:	In the event of fire wear self-contained breathing apparatus.
6. Accidental Release Measures	
Personal Precautions:	Wear protective equipment as specified in Section 8. Do not eat, drink or smoke. Avoid contact with skin and eyes. Avoid breathing vapours. Eliminate all ignition sources.
Environmental Precautions:	Keep people and animals away. Prevent entry into drains, sewers and watercourses. If spillage enters drains leading to sewerage works inform the local water company. If spillage enters rivers or watercourses inform the Environment Agency.
Spillages:	Cordon off area. Avoid sparks and open flames. Absorb/contain spillage using inert absorbent granules, sand or earth. Transfer collected material to heavy-duty plastic/steel drums and keep in a well ventilated place for subsequent safe disposal. See Section 13.
7. Handling and Storage	
Handling:	No specific precautions required when handling unopened containers; follow any relevant manual handling guidance. Refer to Sections 6 and 8 if exposure to product is possible. Take precautionary measures against static discharges. Wash thoroughly with soap and water before eating, drinking or smoking, and after work
Storage:	Store in original containers in a well ventilated area away from heat, sunlight, ignition sources or open flame. Keep away from oxidising agents. Take precautionary measures against static discharges.
8. Exposure Controls / Personal Prot	tection
Occupational Exposure Standards:	Petroleum Solvent: 8 Hour TWA 300ppm, 15min STEL 375ppm (recommended).
Engineering Control Measures:	Refer to any applicable COSHH assessments. Engineering controls should be used where practicable in preference to personal protection and may include physical containment and good ventilation.
Respiratory Protection:	If levels of vapour exceed the above limits use an approved respirator fitted with an appropriate gas cartridge (organic substance). All items must conform to EN149 and should be suitable for the levels of contamination present in the workplace.
Hand Protection:	Wear Neoprene, Nitrile or PVC gloves or gauntlets. These must be manufactured to EN374. The material breakthrough time should be stated by the glove manufacturer, and must be observed at all times.

Safety Data Sheet according to 1907/2006/EC			
Ref: HSD/D3	Issue No: 8	Date of Issue: 24 th October, 2011	
Eye Protection:	If splashing of the product is likely chemical resistant goggles should be worn.		
Body Protection:	Wear suitable imp	ervious, chemical resistant overalls.	
Foot Protection:	Wear chemical res	sistant safety footwear.	
Hygiene Measures:	Handle in accorda and safety practice	nce with good industrial hygiene e.	

9. Physical and Chemical Properties

Appearance:	Black liquid	Boiling Point:		150-200°C
Odour:	Aromatic	Vapour Pressure @ 38°C:		2.0 kPa
pH:	N/A	Evaporation Rate (Butyl Ac	etate = 1):	N/D
Flash Point:	41°C	Flammable Limits in Air:	Upper: Lower:	7.0% 0.6%
Solubility:	Immiscible in wate	er Autoignition Temperature:		230°C
Flammability:	Flammable			
Specific Gravity:	0.9			
10. Stability and Re	activity			
Stability:		Stable under normal conditions (s heat, flames and sparks.	see Section 7	7). Avoid
Materials to Avoid:		Reacts strongly with oxidisers.		
Hazardous Decomposition Products:		Thermal decomposition may lead to the formation of a wide range of compounds, some of which may be hazardous. With incomplete combustion smoke and hazardous fumes and gases, including carbon monoxide, may be formed.		

11. Toxicological Information

There is no data available on the product itself. The following information is based on a knowledge of the components and the toxicology of similar products.

Inhalation:	Vapour concentrations above the recommended exposure levels are irritating to the eyes and respiratory tract, and may cause headaches, dizziness and have other CNS effects.
Skin Contact:	Low order of toxicity. Frequent or prolonged contact may cause irritation and cause dermatitis.
Eye Contact:	Irritating but does not cause tissue injury.
Ingestion:	Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema. Minimal toxicity.

Safety Data Sheet according to 1907/2006/EC

Ref: HSD/D3

Issue No: 8 Date of Issue: 24th October, 2011

12. Ecological Information

There is no data available on the product itself.

The following information is based on a knowledge of the components and the toxicity of similar products.

Mobility:	Floats on water. Partly evaporates from water or soil surfaces, but a
	significant proportion will remain after one day. Large volumes may penetrate soil and could contaminate groundwater.

Ecotoxicity: Expected to be toxic to aquatic organisms.

13. Disposal Considerations

Dispose of unused product as hazardous waste, in accordance with all applicable local and national regulations, and in compliance with the Environmental Protection (Duty of Care) Regulations 1991.

Used containers should be drained thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

14. Transport Information

For 25 Litre Unit:

UN Number: 1263 **ROAD** ADR Class: 3 ADR Hazard Number: 30 **SEA** IMDG Class: 3 EMS: F-E, S-E Marine Pollutant: P Proper Shipping Name: Paint Packaging Group: **AIR** Air Transport Number: Packaging Instruction:

3 366 (Cargo only) 355

Ш

For 5 Litre Unit:

Supplied as Limited Quantity.

15. Regulatory Information

EU Classification and Labelling Particulars:

Designated Name: D-BAR

Classification: Flammable, Harmful & Dangerous for the Environment

Indication(s) of Danger: F,Xn,N

Contains:

Petroleum Solvent

Risk and Safety Phrases:

R10:	Flammable.
R51/53:	Toxic to aquatic organisms, may cause long-term adverse
	effects in the aquatic environment.
R65:	Harmful: may cause lung damage if swallowed.
S24/25:	Avoid contact with skin and eyes.
S43:	In case of fire use foam, dry powder or CO ₂ - NEVER USE
	WATER.

Safety Data Sheet according to 1907/2006/EC Ref: HSD/D3 Issue No: 8 Date of Issue: 24 th October, 2011			
Rei. HSD/D3	13506 140. 0		
S62:	If swallowed, do not induc immediately and show the	ce vomiting. Seek medical advice e container or label.	
UK Guidance Publications:	· · · ·	osure Limits, HSE. Revised annually. Diseases - Health and Safety	
UK Legislation:	Statutory Provisions. Control of Substances Ha The Manual Handling Ope The Personal Protective E 1992.	k, etc Act, 1974, and relevant azardous to Health Regulations, 1999. erations Regulations, 1992. Equipment at Work Regulations, nation and Packaging for Supply) 9 3.	

16. Other Information

Full Text of R-Phrases Referred to above:

R10:	Flammable.
Training Advice:	Do not use unless trained to do so. Refer to the Technical Data Sheet for the product.
Recommended Uses:	For professional use only. This product is designed for use as a dowel bar debonding compound
Further Information:	This Safety Data Sheet was compiled in accordance with EU Directives 67/548/EEC and 1999/45/EC. The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark. ESES (The European Chemical Substances Information System), provided by the European Commission Joint Research Centre in Ispra, Italy. Reference was also made to the above legislation and guidance publications.
MSDS First Issued:	3 rd November, 1989.
MSDS Revised:	24 th October, 2011.
Changes in this Version:	Section 14 revised to reflect change in IATA classification.
Prepared By:	F. Stratton

Disclaimer: The information in this document is offered for general health and safety guidance only and is not intended to be a definitive source of advice, nor does it constitute a risk assessment, for which the user is responsible. All information provided in this document is believed to be accurate to the best of our knowledge. Users of the products referred to should observe the recommendations, conditions and instructions relating to any relevant product label, usage information, consent or approval in force at the time. Further and more specific information may be obtained from the supplier on request.