





HAZ METAL FIXING SYSTEMS

Your Fixing Systems Specialist

Anchor Channel Systems

Technical Product Catalogue
HAZ-CI-EN/04.16



Company Profile

Introduction

HAZ Metal A.S. is located in Iskenderun, in the southern part of Turkey, based in their own property of 17.000 square meters .

The company provides services in the design and production of fixing systems for facade cladding, framing channel systems, brick support systems, cast-in channels and a variety of products used in construction.

The company's mission statement is to assist and advise its clients in choosing the most suitable fixing systems for their requirements and to provide them with quality production and supply with timely deliveries.

The innovative design and production techniques offer practical and economic solutions to solve every possible problem within the scope of fixing applications in construction.

As a manufacturer of fixing systems to major projects around the world, HAZ Metal has proven its quality and reliability to its clients. The company enjoys serving the sector and works hard to constantly improve and develop its services.

HAZ Metal is dedicated to achieving the highest level of customer satisfaction and is always in constant contact with its clients in order to better understand their requirements and to offer the services required for design and production of fixing systems.

Channel Production

The production of cast in channels has been made in HAZ Metal since the year 2001.

Throughout the years, production techniques and methods have been improved to achieve higher quality and productivity. Haz Metal today implements modern technology in the production of channels in order to meet the requirements of the industry.

The factory channel production unit is equipped with a coil slitting machine, channel roll formers, press breaks and production units with 250 ton eccentric presses used for the pressing of the studs on to the channels. There is also an in house electro-galvanizing pool where 12 micro thick zinc coating on mild steel is made. Hot dip galvanizing with over 50 micro thick zinc coating is made by prequalified sources.

The presence of a work shop with the capability of preparing and maintaining the required moulding and tooling, provides flexible production. The urgent preparations, maintenance, revision and adjustment of machines and tooling are made without interrupting the production process which leads to saving time and costs.

The production is strictly controlled with periodic in house testing of both raw materials and finished products, in order to maintain the performance of HAZ products and to fulfil the safety requirements for use in the construction industry.



Production Capacity

HAZ Metal is capable of producing a minimum of three thousands six hundreds metric tonnes of cast in channels yearly.

Roll forming technology is used to produce cold roll formed channels. Anchor studs are cold forged with bolt maker machines. Swaging of the anchor studs on to the channels is done with fully automated lines to achieve the highest quality standards.

To achieve the highest quality standards in our production, most of the production is made with fully automated lines, PLC systems that has significant precision and accuracy, so as to reduce human errors.

The factory is one of the only manufacturer which produces it's own dies and moulds. This ensures high quality and flexibility with results in high competitiveness in pricing and lead time.

Technical Know-How

HAZ Metal has a dedicated and professionally trained team which emphasizes in improving the efficiency and effectiveness of their production.

Technical training is conducted regularly to ensure that technical know-how of the production and engineering processes persists within the organization.

Quality Standards

HAZ Metal adopts EN standards in the production of channels. Production is strictly controlled in accordance with these standards.

To achieve its objectives and maintain high level of consistency, HAZ Metal adopts the highest international standards and global best practice.

The company quality management system complies with the requirements of ISO 9001:2008. A quality assurance system and controlled checks are documented in the manufacturing process.



Coil slitting line



22 stand channel rolling machine



16 stand channel rolling machine



Automated stamping unit

HMPR-CE Anchor Channels - Introduction

HMPR-CE Anchor Channels are rolled channels with swaged studs that are used for connections made to concrete structures. This system allows easy and safe fixations to structures such as concrete slabs, beams and columns.

HTB T head bolts and **HMLN** lock nuts to allow secure and easy connections on to anchor channels. The use of this system is applicable in a wide range of construction works.

Features of **HMPR-CE** cast in channels are as follows:



- **HMPR-CE** Anchor Channels are designed in accordance with the design rules according to CEN / TS 1992-4-3.
- **HMPR-CE** Anchor Channels allow users working with low edge distances.
- Load resistances can be improved by using higher concrete strength class on loading.
- Shear and tensile resistance in concrete can be improved with additional reinforcement.

HMPR-CE Anchor Channels are manufactured by HAZ Metal A.S. in Turkey with engineering and product development provided from its sister company in Germany, HAZ Deutschland GmbH. Since 2004 HAZ Metal has built an effective product development system to increase the integrity of its products and production.

HMPR-CE channels have been tested in IFBT Leipzig in accordance to the EOTA guidelines and have received good results. The **HMPR-CE** cast in channels have been awarded an ETA certificate.

HMPR-CE anchor channels can be used safely and efficiently with the following features:

- Quality production with strict control according to European requirements
- Management and Service quality certified by ISO 9001:2008
- Euro code compatible design and product dimensioning using product selection software
- Customized design in providing solutions to meet special product requirements



HAZ Metal management system is certified to ISO 9001:2008 standards by TUV SUD



• **HMPR** Cold rolled cast in channels

• **HMPR-S** Toothed, cold rolled cast in channels

• **HMPR-H** Hot rolled cast in channels

HMPR-CE Anchor Channels - Introduction



Advantages

- No drilling on site
- Quick and easy fixing
- Fixing without damaging concrete
- Adjustable and flexible
- Safe near edges on concrete
- High load capacity
- Fixing without electrical tools
- Safe and secure fixing
- No dust particles falling onto facade
- No electricity needed
- Easy connections with T head bolts and lock nuts
- Compensation of tolerances of the structure
- Fixtures are removable and new fixing can be made

Planning


Careful planning needs to be done prior to concrete casting. Anchor channel types should be determined according to the load capacities, edge distances, area of applications etc. Anchor channel positioning should be incorporated in to the shop drawings of the form works in order to provide clear instructions for installation on site.

Applications


Anchor channels are widely used for the installation of curtain walls. Unitised panels with materials such as glass and natural stone already incorporated are preassembled in to the curtain wall panels. These panels are erected on to the facades and are quickly and easily fixed on to anchor channels using T head bolts and special brackets.



Anchor channels are used for a variety of construction applications which require attachments made on to concrete. Pipe and duct installation and the installation of electrical wiring are the most common applications that are made using anchor channels.



Brick walls are installed using special support brackets that are fixed on to anchor channels using T head bolts. A continuous anchor channel embedded into the concrete wall provides high adjustability and enables quick installation of the masonry brackets. Anchor channels cover the load capacity requirements for the masonry facade installation.



The prefabricated concrete industry is among the fastest growing fields within the construction industry. The use of Anchor channels enhance the fast and economical solutions that are offered using prefabricated concrete panels. Speed and security are the benefits of using Anchor channels.



ETA - European Technical Approvals

European Technical Approval ETA

In June 2013 **HMPR-CE** anchor channels have been certified with an ETA certificate from DIBT (German Institute of Building Technology). **HMPR-CE** anchor channels are Euro code compatible that are designed and dimensioned according to CEN/TS 1992-4 standard in combination with the approved loadings in the HAZ ETA approval. The channels that are dimensioned according to CEN/TS 1992-4 standard are distinguished with a code HMPR-CE and the products are stamped with the CE marking.

The ETA approval includes thorough specifications on internal and third party quality control of on-going production. Therefore quality assurance is in place to be certain that the quality of the **HMPR-CE** channels correspond with the samples tested during the approval procedure.

European Standard CEN/TS 1992-4

The European CEN standard has been created for the purpose of standardising the dimensioning of fastenings in to concrete structures. Any connections in to concrete such as anchor bolts and anchor channels are regulated with this standard.

CEN/ TS standards committee for the Design of fastenings for concrete was founded in 2000. In 2009 the set of regulations were published as CEN/TS 1992-4. This technical specification document is treated as a preliminary standard with an objective to turn in to a European standard. With the publication of this standard a representation of advanced fixing technology is used in practice.

Benefits of using HMPR-CE Anchor Channels

A comprehensive test program is conducted on the products in accordance to the new guidelines of ETA. Channels are wet tested to consider failure loads on channels, studs and concrete in various situations such as load direction and reduced edge distances.

With the resistance loads derived from extensive testing, greater flexibility is achieved in the design of connections into concrete. Regarding whether the concrete is reinforced or non-reinforced, cracked or uncracked, load carrying connections can be provided. Therefore numerous options are achieved which influence the results. These values can be used to achieve the most economic and effective solution for the application at hand.

The advantages of the **HMPR-CE** channels can be summarized as below:




- Possibility to consider various concrete strength classes
- Recognizing reinforcement when designing the location of the anchor channel
- Highest cost effectiveness in choosing the most effective selection
- Small edge distances are possible with verified loadings
- Increased loads with additional or closely positioned reinforcements
- Optimised design by taking into account concrete strength, reinforcement lay out and component thickness.

ETA - European Technical Approval



The European Technical Approval ETA- 13/0399 for the HMPR-CE Anchor Channels was issued by the Deutsches Institut für Bautechnik (DIBt) in 2013. This new approval is valid on all states of Europe.

This ETA catalogue includes the dimensioning of the anchor channels in accordance with the new European standards series CEN/TS 1992-4-3 "Design of fastenings for use in concrete - Anchor Channels".



Product Verification Method according to ETA

CEN-TS 1992-3 Standard

CEN TS/1992-4 part 3 standard lays down a newly developed method for the design and dimensioning of anchor channels. The verification guideline is shown in the following table.

Verifications for HMPR-CE anchor channels acc. to CEN/TS 1992-4-3					
Tension Loading			Shear Loading		
Failure Mode			Failure Mode		
Steel Failure	Anchor	$N_{Ed} \leq N_{Rd,s,a}^a$	Steel Failure	Anchor	$V_{Ed}^a \leq V_{Rd,s,a}^a$
	Connection between anchor and channel	$N_{Ed} \leq N_{Rd,s,c}^a$		Connection between anchor and channel	$V_{Ed}^a \leq V_{Rd,s,c}^a$
	Local flexure of channel lip	$N_{Ed} \leq N_{Rd,s,l}^a$		Local flexure of channel lip	$V_{Ed} \leq V_{Rd,s,l}^a$
	Special screw	$N_{Ed} \leq N_{Rd,s,s}^a$		Special screw	$V_{Ed} \leq V_{Rd,s,s}^a$
	Flexure of channel	$M_{Ed} \leq M_{Rd,s,flex}$	Pry-out failure		$V_{Ed} \leq V_{Rd,cp}^a$
Pull-out failure		$N_{Ed} \leq N_{Rd,p}$	Concrete edge failure		$V_{Ed}^a \leq V_{Rd,c}^a$
Concrete cone failure		$N_{Ed} \leq N_{Rd,c}$			

* On verification table, N_{Ed} and V_{Ed} loads represent design tensile and shear loads of channels which act on the bolt, while N_{Ed}^a and V_{Ed}^a are the loads that result on studs of the channel.

* All proofs of failure types should be checked acc. to verification table.

Dimensioning Software

The new HAZ CCP (Anchor Channel Calculation Program) for calculating HAZ Anchor channels with rules of European Technical Approval (ETA) is a convenient and very powerful tool for users.

With this program, users will be able to design channels in a few seconds concerning with various parameters such as concrete grade, small edge distances, additional reinforcements, loads types and so on. That would require an optimum design for the user.

Channel & bolt
The type and size of the product under analysis are entered in this field

Concrete & dimension
The concrete strength and the concrete member dimensions entered in this field

Reinforcement
Information on the availability and type of reinforcement is entered in this field

Additional reinforcement
Information on additional reinforcement for tension and shear


Loads
Information on loading applications are entered in this field

Result
The results of design resistances of the product are displayed in this section

Graphics screen
Input information is displayed in the graphics screen

HMPR-CE Anchor Channels - Product Range

HMPR - Cold rolled anchor channels



HMPR Cold rolled channels are suitable to with stand static loads. The range available can cover resistance loads ($N_{Rd} = V_{Rd}$) between 7,22 kN and 50,56 kN. Channels are available in stainless steel 1.4301 & 1.4401 and hot dip galvanised mild steel 1.0038 & 1.0976 (S235JR & S355MC).


Product Code	HMPR-CE 72/49	HMPR-CE 54/33	HMPR-CE 49/30	HMPR-CE 40/25	HMPR-CE 38/17	HMPR-CE 28/15
Channel Section	72/49	54/33	49/30	40/25	38/17	28/15
Load Capacity (kN) $N_{Rd} = V_{Rd}$ Steel / Stainless steel	45.00/50.56	41.67/36.67	17.22/25.00	12.22/15.00	10.56/12.22	7.22/8.33
Channel Flexure (Nm) Steel / Stainless steel $M_{Rd,s,flex}$	9868/6408	2832/2696	1646/1600	1356/1048	595/651	349/348

Product Code	HTB-72	HTB-54	HTB-50	HTB-40	HTB-38	HTB-28
Metric size	M20,M24,M30	M12,M16,M20	M12,M16,M20	M10,M12,M16	M10,M12,M16	M8,M10,M12
T.Bolt min spacing (mm) S_{slb}	121	80	74	64	47	41

HMPR-H Hot rolled Anchor Channels - Product Range

HMPR-H

Hot rolled cast-in channels



HMPR-H Hot rolled channels are suitable to withstand dynamic loads as well as static loads. These channels are available in hot dip galvanized and mild steel finish 1.0038 (S235JR).

Product Code	HMPR-H 52/34	HMPR-H 50/30	HMPR-H 40/22
Channel Section	52/34	50/30	40/22
Load Capacity (kN) $N_{Rd} = V_{Rd}$ Steel / Stainless steel	30.5/ -	17.2/	11.1/ -
Channel Flexure (Nm) Steel / Stainless steel $M_{Rd,s,flex}$	3226/ -	2703/ -	1260/ -

Product Code	HTB-72	HTB-54	HTB-50
Metric size	M20,M24,M30	M12,M16,M20	M12,M16,M20
T.Bolt min spacing (mm) S_{slb}	81	73	58

HMPR-S

Cold rolled toothed cast-in channels



HMPR-S Cold rolled toothed channel 41/22 can be used for longitudinal loads. This channel is available in stainless steel 1.4301 & 1.4401 and hot dip galvanised mild steel 1.0038 (S235JR).

HMPR-S 41/22
41/22
15.8
595 / 651

HTS-41
M12,M16
28

HMPR-CE Anchor Channels - Standard Lengths

Standard Channel Lengths


The list of the standard product range is showed on the table in accordance with European Technical Approval requirements. Other lengths and anchor numbers can be supplied depending on request.

For further information please contact us.

Product Length Range of HAZ HMPR-CE Anchor Channels - Length / Number of Anchors									
Cold Rolled Channels							Hot Rolled Channels		
HMPR 72/49	HMPR-CE 54/33	HMPR-CE 49/30	HMPR-CE 40/25	HMPR-S 41/22	HMPR-CE 38/17	HMPR-CE 28/15	HMPR-H 52/34	HMPR-H 50/30	HMPR-H 40/22
170/2	170/2	150/2	150/2	150/2	100/2	100/2	170/2	150/2	150/2
200/2	200/2	200/2	200/2	200/2	150/2	150/2	200/2	200/2	200/2
250/2	250/2	250/2	250/2	250/2	200/2	200/2	250/2	250/2	250/2
300/2	300/2	300/2	300/2	300/2	250/2	250/2	300/2	300/2	300/2
350/2	350/3	350/3	350/3	350/3	300/3	300/3	350/3	350/3	350/3
450/3	400/3	400/3	400/3	400/3	350/3	350/3	400/3	400/3	400/3
650/3	550/3	550/3	550/3	550/3	450/3	450/3	550/3	550/3	550/3
970/4	820/4	800/4	800/4	800/4	550/4	550/4	820/4	800/4	800/4
	1070/5	1050/5	1050/5	1050/5	850/5	850/5	1070/5	1050/5	1050/5
	3070/13	3050/13	3050/13	3050/13	1050/6	1050/6	3070/13	3050/13	3050/13
	6070/25	6050/25	6050/25	6050/25	3050/16	3050/16	6070/25	6050/25	6050/25
					6050/31	6050/31			
130 ≤ Ss ≤ 400	100 ≤ Ss ≤ 250				50 ≤ Ss ≤ 200		100 ≤ Ss ≤ 250		
Ss = Anchor spacing									


Standard short length channels

Short length channels are available from 100 mm to 950 mm with stud quantities and spacings according to the table above.




Standard long length channels


Long length channels are supplied in 1050, 3030 and 6070 mm lengths with varying stud spacings according to section type of the channel.



Types of round anchors studs

Type	Anchor	Shaft d1	Head d2	min hef
[mm]				
Round Studs	28/15	6	12	45
	38/17	8	16	76
	40/25	8	16	79
	49/30	10	20	94
	54/33	12	24	155
	72/49	16	32	179
	40/22	8	16	76
	50/30	10	20	94
	52/34	16	32	156





Renaissance Tower, Istanbul

Contents


Company Profile	1	Anchor Channels for Balustrades	26
HMPR-CE Anchor Channels Introduction	3	HAZ-TU Anchor Channels for Profiled Sheets Introduction	27
ETA - European Technical Approval	5	HAZ-TU Anchor Channels Product Details	28
Product Verification according to ETA	6	HAZ-TU Anchor Channels Technical Details	29
HMPR-CE Anchor Channels Systems Product Range	7	HAZ-TU SL Self Locking Anchor Channels Product Details	30
HMPR-CE Anchor Channels Standard Lengths	9	HCPLS Anchor Plates Product Details	30
HMPR-CE Anchor Spacing & Minimum Edge Distances	10	HWT Wall Tie Introduction & Details	31
HMPR-CE Installation detail & section views	11	HWT-M Wall Ties Introduction	32
HMPR-CE Marking & Material grade	12	HBTR Brick Tie Channel Product Details	33
HMPR-CE Compatible T head Bolt Dimensions	13	HWT-M Wall Ties For Masonry Product Details	34
HMPR-CE Compatible T head Bolt Load Properties	14	HTB T Bolts & HMLN Lock Nuts Introduction	35
HMPR-CE Anchor Channels Load Tables	15	HTB T Bolts & HMLN Lock Nuts Technical Details	37
HMPR-CE Anchor Channels Technical Summary	16	Anchor Channel Application Examples	39
HMPR-CE Anchor Channels Dimensioning Principles	17	Support Brackets for facade applications	41
Methods of Verification Against Failures	18	Box channel solution for Facade Applications	43
Quality Assurance Control	19	Anchor channel application pictures	44
HMPR-CE Installation Information	21	Project References	45
Special Types of Anchor Channels	23		
Anchor Channels for Metal Decks	25		

HMPR-CE Anchor Spacings & Minimum Edge Distances

Anchor stud spacings

In order to meet the resistance loads, anchor stud spacings should be positioned according to the tables below.


Anchor Channel	Anchor Spacing		End Spacing (x)	min channel length (mm l)
	smin	smax	round anchor	round anchor
	(mm)			
28/15 38/17	50	200	25	100
40/25 40/22 49/30	100	250	25	150
50/30 54/33 52/34	100	270	35	170
72/49	130	400	35	200



Minimum edge distances

Depending on the type of the channels, anchors studs must be positioned at a minimum distance from the component edges.

The minimum spacings of the T head bolts must be adhered to according to the table below.




Anchor Channel		28/15			38/17			40/25 & 40/22			49/30 & 50/30			54/33 & 52/34			72/49			
Special screws	M	[mm]	8	10	12	10	12	16	10	12	16	12	16	20	12	16	20	20	24	30
Min. spacing of screws	S _{s,min}		40	50	60	50	60	80	50	60	80	60	80	100	60	80	100	100	120	150
Min. anchorage dept	min hef		45			76			79			94			155			179		
Min. edge distance	C _{min}		40			50			50			75			100			150		
Min. member thickness	h _{min}		hef + D _h + C _{nom}																	

Installation Details & Section Views

Installation of the anchor channels

The fitness for use of the anchor channel can be guaranteed according to the following installation conditions:


- The installation of the anchor channels must be made with qualified workers
- Installation must be made with the manufacturers specifications and drawings
- Fixing on the form work must be done in a way that no movement of the channels will occur during laying of the reinforcement bars and pouring and compacting of the concrete
- The concrete under the head of the anchor channels must be properly compacted
- Size and positioning of the t head bolts must correspond to the specifications and drawings
- Setting torques of the T head bolts must not be exceeded



Typical Section Views

Legend:

- h_{ch} channel height
 b_{ch} Width of channel
 h_{ef} anchorage depth
 h_{nom} Embedment depth




HMPR-CE Anchor Channels - Product Range

Marking


Marking of the HAZ - anchor channel : e.g. HAZ 54/33 - A4

HAZ = Identifying mark of the manufacturer
54/33 = Size
A4 = Material



Marked on back of channel

or



Marked inside of channel

Material channels:


A2 = 1.4301

A4 = 1.4401 / 1.4404 / 1.4571

HDG = 1.0038 / 1.0044

Marking of the HAZ - special screw e.g. HS A4-70

HS & HAZ = Identifying mark of the manufacturer
A4-70 = Material / Strength grade



Material / Strength grade special screws:

4.6 = Strength grade 4.6

8.8 = Strength grade 8.8

A4-50 = Stainless steel (1.4401 / 1.4404 / 1.4571)
Strength grade - 50

A4-70 = Stainless steel (1.4401 / 1.4404 / 1.4571)
Strength grade - 70

L4-70 = Stainless steel (1.4362 / 1.4462) Grade - 70

Material Types


Materials and intended use				
	Dry conditions	Internal conditions with usual humidity	Medium corrosion exposure	High corrosion exposure
Specification	Material types required for use in structures subject to dry internal conditions with the exception of usual humidity (e.g. accommodations, offices, schools, hospitals etc.)	Material types required for use in structures subject to internal conditions with usual humidity (e.g. kitchen, bath and laundry in residential buildings)	Material types required for use in structures subject to external atmospheric exposure (including industrial and marine environment) or in permanently damp internal conditions.	Material types required for use in structures subject to exposure in particular aggressive conditions (e.g. immersion of sea water, chloride atmosphere) or atmosphere with chemical pollution (e.g. in desulphurization plants)
Channel material grade	Steel 1.0038;1.0044 EN 10025 hot-dip-galv ≥ 50 µm	Steel 1.0038;1.0044 EN 10025 hot-dip-galv ≥ 50 µm	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088
Anchor material grade	Steel 1.0038;1.0214,1.0401 1.1132,1.5525 EN 10263 hot-dip-galv ≥ 50 µm	Steel 1.0038;1.0214,1.0401 1.1132,1.5525 EN 10263 hot-dip-galv ≥ 50 µm	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088
T head bolt material grade	Steel strength grade 8.8/4.6 EN ISO 898-1 e-galv ≥ 5 µm	Steel strength grade 8.8/4.6 EN ISO 898-1 hot-dip-galv ≥ 50 µm	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 3506-1	Stainless steel 1.4462/1.4529/1.4547 EN 3506-1
Washer material grade	Steel EN 10025 e-galv ≥ 5 µm	Steel EN 10025 hot-dip-galv ≥ 50 µm	Stainless steel 1.4401/1.4404/1.4571 EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088
Nut material grade	Steel strength grade 8.8 EN 20898-2 e-galv ≥ 5 µm	Steel strength grade 8.8 EN 20898-2 hot-dip-galv ≥ 50 µm	Stainless steel 1.4401/1.4404/1.4571 EN ISO 3506-2	Stainless steel 1.4462/1.4529/1.4547 EN ISO 3506-2
1) Available on request 2) Steel acc. to EN 10025, 1.0038 not or anchor channels 28/15 and 38/17 3) Electroplated acc. to EN ISO 4042 4) Hot-dip galvanized on the basis of EN ISO 1461, and coating thickness ≥ 50 µm				

HMPR-CE Anchor Channels - Product Range

Dimensions of the HAZ METAL Special Screws & Strength Grade



Hammer-head screw

Fig. 1



Hook-head special screw

Fig. 1



l_{erf} = Bolt length
 i = channel lip thickness
 t_{fix} = Fixture thickness
 s = washer thickness
 V = minimum thread length

Dimensions of the HAZ METAL Special Screws:

Anchor Channel	Fig.	Dimensions				Length l
		b1	b2	k	Ø	
		[mm]				[mm]
28/15	1	10	23	4	8	15-200
	1	10	23	5	10	20-300
38/17	1	13	31	6	8	20-300
	1	13	31	6	10	20-300
	1	13	31	7	12	20-300
	1	13	31	7	16	20-300
40/25	2	14	35	7,5	10	20-300
	2	14	35	7,5	12	20-300
	2	14	34	8,5	16	20-300
49/30 54/33	2	13	43,3	10	10	20-300
	2	13	43,3	10	12	20-300
	2	17	43,3	11	16	20-300
	2	21	43,3	12	20	30-300
72/49	2	23	58	14	20	50-300
	2	25	58	16	24	50-300
	2	31	58	20	30	50-300

Special Screws	Steel ¹⁾		Stainless Steel ¹⁾	
Strength grade	4.6	8.8	A4-50	A4-70
f_{uk} [N/mm ²]	400	800	500	700
f_{yk} [N/mm ²]	240	640	210	450
Finish	z.p., h.d.g			

1) Materials according to Annex 3, Table 1

• The length of the T bolt must be determined using the formula
 $(L_{erf} = t_{fix} + i + s + v)$

Dimensions V_{min}


T head bolt Metric size	V_{min} (mm)
M8	12.5
M10	14.5
M12	17.0
M16	20.5
M20	26.0
M24	29.0
M30	33.5

Dimensions of channel lip i

Anchor Channel	i (mm)
28/15	2.25
38/17	3.00
40/25	5.60
49/30	7.39
54/33	7.90
72/49	9.90


T head Bolt Load Properties

T head bolts characteristic load values




T Head Bolt		M8	M10	M12	M16	M20	M24	M30
max fixture hole dia. (mm)		9	12	14	18	22	26	33
4.6	N Rd	7.3	11.6	16.9	31.4	49.0	70.6	112.2
	V Rd	4.3	6.9	12.1	22.6	34.7	50.7	80.6
	M Rd	9.0	17.9	31.4	79.8	155.4	268.9	538.7
8.8	N Rd	19.5	30.9	44.9	76.0	122.0	165.6	242.5
	V Rd	11.7	18.6	27.0	50.2	78.4	99.2	145.6
	M Rd	24.0	47.8	84.0	213.0	415.4	718.4	1439.2
A4-50	N Rd	6.4	10.1	14.8	27.4	42.8	61.7	98.1
	V Rd	3.8	6.1	10.6	19.8	30.9	44.5	70.7
	M Rd	7.9	15.7	27.5	70.0	136.3	235.8	472.5
A4-70	N Rd	13.7	21.7	31.3	58.8	82.4	132.1	210.0
	V Rd	8.2	13.0	18.9	35.2	49.2	95.1	151.0
	M Rd	16.8	33.5	58.8	149.4	291.3	503.7	1009.2

Minimum spacing and setting torque of T head bolts



General:

The fixture is braced to the concrete and channel respectively. The stated torque values must not be exceeded.




Steel to steel:

The fixture is braced to channel with use of a suitable washer. The stated torque values must not be exceeded.

Cast-in Channel	T Head Bolt Diameter	T bolt spacing $S_{s,min}$	Setting Torque T_{inst}		
			General	Steel-steel contact 8.8	Steel-steel contact A4-70
28/15	M8	40	8	20	20
	M10	50	13	40	40
	M12	60	15	50	50
38/17	M10	50	15	40	40
	M12	60	25	70	70
	M16	80	45	100	120
40/25	M10	50	15	40	40
	M12	60	25	70	70
	M16	80	45	150	150
49/30	M12	60	25	70	50
	M16	80	60	180	180
	M20	100	75	90	190
54/33	M12	60	25	70	50
	M16	80	60	180	180
	M20	100	120	120	320
72/49	M20	100	120	360	-
	M24	120	200	360	-
	M30	150	380	400	-

HMPR-CE Anchor Channels Load Tables & Calculation Examples


Single Loading



Channel Type	T Head bolt	Minimum edge distance ar (mm)	Component minimum thickness h (mm)	Resistance Load FRd (kN) Resultant load / Single Loads						
				Channel length L (mm) / no of anchor studs						
				150 (2)	200 (2)	250 (2)	300 (2)	350 (2)	350 (3)	1050
28/15	M8,10,12	65	100	6.5	6.9	6	-	-	6.9	5.6
38/17	M12,16	100	130	10.5	10.5	10.3	-	-	10.5	8.3
40/25 40/22	M16	130	150	12.2	12.2	12.2	12.2	-	12.2	7.4
49/30 50/30	M16,20	195	180	17.2	17.2	17.2	17.2	-	17.2	9.3
54/33 52/34	M20	260	250	39.5	40.8	41.1	41.3	-	39.8	13.9
72/49	M24,30	325	300	-	44.8	44.9	44.9	44.9	-	17

Concrete grade 30/37


Pair Loading



Channel Type	T Head bolt	Minimum edge distance ar (mm)	Component minimum thickness h (mm)	Resistance Load FRd (kN) Resultant loads / Pair Loads				
				Channel length L (mm) / no of anchor studs				
				200 (2)	250 (2)	300 (2)	350 (2)	350 (3)
28/15	M8,10,12	65	100	4	-	4.3	-	4.3
38/17	M12,16	100	130	6.6	-	6.8	-	7.2
40/25 40/22	M16	130	150	8.6	8.8	-	-	9.2
49/30 50/30	M16,20	195	180	13	13.4	-	-	13.7
54/33 52/34	M20	260	250	20.9	21.3	-	-	21.5
72/49	M24,30	325	300	27.2	27.7	-	28.1	-
Minimum t bolt spacing s_min (mm)				100	125	125	150	150

Concrete grade 30/37


Load arrangement

Resultant Designed Load F_{Ed} 


N_{Ed} = Design value of an action tensile load
 V_{Ed} = Design value of an action shear load
 F_{Ed} = Design value of an action resultant load

$$F_{Ed} = \sqrt{N_{Ed}^2 + V_{Ed}^2}$$

Single loading - long channels



Pair loading - long channels



Calculation examples

Example 1:

Tension $N_{Ed} = 5,0$ kN
 Shear $V_{Ed} = 4,0$ kN
 Resultant $F_{Ed} = \sqrt{5,0^2 + 4,0^2} = 6,4$ kN

Chosen $\rightarrow$ HMPR-28/15-150: F_{Rd} 6,5 kN

Example 2:

Tension $N_{Ed} = 10,5$ kN
 Shear $V_{Ed} = 0$ kN
 Resultant $F_{Ed} = \sqrt{10,5^2 + 0^2} = 10,5$ kN










Chosen $\rightarrow$ HMPR-38/17-200: F_{Rd} 10,5 kN

Example 3:


Tension $N_{Ed} = 0$ kN
 Shear $V_{Ed} = 15,0$ kN
 Resultant $F_{Ed} = \sqrt{0^2 + 15,0^2} = 15,0$ kN

Chosen $\rightarrow$ HMPR-49/30-200: F_{Rd} 15,0 kN


HMPR-CE Anchor Channels Technical Summary

Profiles		Cold rolled channels					Hot rolled channels			
		HMPR 72/49	HMPR-CE 54/33	HMPR-CE 49/30	HMPR-CE 40/25	HMPR-CE 38/17	HMPR-CE 28/15	HMPR 52/34	HMPR 50/30	HMPR 40/22
Section view										
Material		A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	HDG	HDG	HDG
Bolt Type		HS	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ
Bolt		72/48	50/30	50/30	40/22	38/17	28/15	50/30	50/30	40/22
M		20-24-30	10-12-16-20	10-12-16-20	8-10-12-16	8-10-12-16	8-10-12	10-12-16-20	10-12-16-20	8-10-12-16
S _{slb} [mm]		121	80	74	64	47	41	81	73	58
Design Resistance Capacities of Profiles (Design values)										
N _{Rd,s,l} = N _{Rd,s,c} [kN]		45	41.6	17.2	12.2	10.6	7.2	30.6	17.2	11.1
V _{Rd,s,l} [kN]		45	41.6	17.2	12.2	10.6	7.2	30.6	17.2	11.1
M _{Rd,s,flex} [Nm]	HDG	9868	2832	1646	1179	517	303	3226	2703	1260
	St.St.	6408	2696	1600	911	566	302	2696	1600	911
Geometric values										
b _{ch} [mm]		72	54	49	40	38	28	52	50	40
h _{ch} [mm]		49	33	30	25	17	15	34	30	22
h _{nom} [mm]		182	157	96	81	78	47	158	96	78
h _{ef} [mm]		179	155	94	79	76	45	156	94	76
c _{min} [mm]		150	100	75	50	50	40	100	75	50

Cold rolled channel



Hot rolled channel



HMPR-CE Dimensioning Principles

Required information for channel selection

The information below are required to conduct a full analysis in order to dimension and select the most secure and suitable anchor channel for the fixing application:

- Anchor channel type & Type of raw material
- Anchor channel length with number of studs and stud spacing distances
- Positioning of the cast in channel in the concrete component with exact edge distances of the channel on all directions
- Thickness of the concrete component and the strength class of the concrete
- Allocation & layout of reinforcement bars within in the concrete component
- Type and size of t head bolts and their numbers
- Fixture application dimensions & type of fixing whether top of slab or edge of slab
- Tensile and shear loadings on the fixture

Verification areas when selecting an anchor channel

The assessment of the suitable anchor channel dimensions for the intended use with regards to the requirements of the mechanical resistance, stability the safety of the application is done by checking the following areas.

Verifications under tension loads	
1. Distribution of acting tension loads	
2. Steel failure - anchor stud	$N_{Rk,s,a}$
3. Steel failure - t head bolt	$N_{Rk,s,s}$
4. Steel failure - connection between channel & anchor stud	$N_{Rk,s,c}$
5. Steel failure - local flexure of channel lips	$N_{Rk,s,l}$
6. Steel failure - flexure resistance of channel	$M_{Rk,s,flex}$
7. Steel failure - transfer of setting torque into prestressing force	T_{inst}
8. Concrete failure - pullout	$N_{Rk,p}$
9. Concrete failure - concrete cone	$N_{Rk,c}$
10. Concrete failure - splitting due to installation	$C_{min}, S_{min}, h_{min}$
11. Concrete failure - splitting due to loading	$N_{Rk,sp}$
12. Concrete failure - blow out	$N_{Rk,cb}$
13. Reinforcement	$N_{Rk,re}, N_{Rd,a}$
14. Displacement under tension loads	σ_N

Verifications under tension loads	
1. Distribution of acting shear loads	
2. Steel failure without lever arm - t head bolt	$V_{Rk,s,s}$
3. Steel failure without lever arm - flexure channel lips	$V_{Rk,s,l}$
4. Steel failure with lever arm	$M_{Rk,s}^0$
5. Concrete failure - pry out	$V_{Rk,cp}$
6. Concrete failure - concrete edge	$V_{Rk,c}$
7. Reinforcement	$V_{Rk,c,re}$
8. Displacement under shear loads	σ_V

Methods of Verification Against Failures

Anchor channel verification against steel breakout


- Correct channel selection by comparing allowable loads and applied loads
- Determination of the anchor loads from tensile loads and shear forces according to the load influence model verification of the connection between anchor and channel
- Arrangement of the bolts along the channels length



Breakout of T head bolt under tensile loading



Breakout of channel lips under tensile loading




Breakout due to flexure of channel under tensile loading



Breakout of channel stud under tensile loading



Breakout of stud under tensile loading




Breakout of T head bolt under shear loading




Breakout of channel lips under shear loading

Concrete verification against failures

- Thickness of the concrete component
- Strength class of the concrete
- Condition of the concrete, cracked or non cracked as a special case to be verified
- Verification against concrete edge distance and channels spacings




Failure of concrete cone under tensile loading



Pull out of channel from concrete under tensile loading



Splitting of concrete under tensile loading



Failure of concrete edge under shear loading



Failure of concrete pry out under shear loading



Blow out of concrete under tensile & shear loading

Quality Assurance Control

HAZ Metal readily embraces the responsibility of the business that it is in. The company has established a well planned quality management system and has been awarded the ISO 9001:2008 quality management certificate.

This system is a part of HAZ Metal's operations and there are no exceptions or compromises in jeopardising the level of quality of the products under production. The QAC department is staffed with knowledgeable and experienced engineers who are trained in the field and form the backbone of this operation.

The factory is equipped with testing machines which are used to conduct chemical and physical tests on all items that enter and exit the warehouse. The production is strictly controlled with periodic in house testing of both raw materials and finished products. This procedure is a part of day to day operations in order to maintain the performance of HAZ products and to fulfil the safety requirements for use in the construction industry.

1.)

150 kN standing tensile load testing machine. Mechanical testing for manufactured products are carried out using this machine

1.)



2.)

2.)

Mechanical testing laboratory with computer aided operations to prepare internal reports and record test results



3.)

Spectrometer is used for conducting chemical composition analysis for the raw materials and the end product components that are sourced outside production

3.)



4.)

4.)

100 kN mobile anchor tensile load testing machine. Testing for performance of products on substrates are carried out using this machine



5.)

Galvanized coating micro thicknesses are checked using electronic gauges to ensure that corrosion protection is in place for steel products


5.)



6.)

6.)

Material thicknesses are checked using digital micrometers to ensure that the products are produced according to tolerance thicknesses




HMPR Anchor Channels - Installation Information

Load Direction


Tensile loading

The loading acts within 150 degrees area towards the face of the channel. Any load acting within this area should be checked with the allowable tensile loads for each channel to choose the appropriate channel.




Shear loading

The loading acts within 15 degree angle towards the lower or upper face of the channel. Any load acting within this area should be checked with the allowable shear loads for each channel to choose the appropriate channel.




Resultant loading

The resultant loading is a combination of both tensile and shear loads. Correct calculation must be made in order to determine the acting load and choose the appropriate channel.




Longitudinal loading


The loading acts along the length of the channel. Each channel has a limited longitudinal load capacity. For strong longitudinal loading a toothed channel must be used.



Installation Instruction




1.) Anchor channels are fixed to form work after careful planning and positioning. Concrete is then cast in to the form work.



2.) After the concrete is cured, the filler inside the channel, set for the purpose of preventing concrete filling the channel's slot, is removed as shown.



3.) Connections to the cast in channels are made with T bolts and lock nuts. T bolts are inserted in to the channels horizontally and then turned right through 90 degrees. This locks them vertically in the channel.




4.) Fixtures are fastened with the T bolts and nuts as shown above. Correct loading and torque values need to be applied in accordance with the allowable loads of the channels and bolts.

HMPR Anchor Channels - Installation Information


Length Cutting At Construction Site

Standard long lengths can be cut to size on construction sites according to the desired length. Care should be taken in making sure that the minimum distance of 25 mm between the studs and channel end should be met.



- Long lengths can be cut to size providing the X size is no less than 25 mm.


- An end anchor is available to be fixed at the end of the cut channel to avoid wastage.




Attachment To Form Work

It is important to firmly attach the anchor channels on to form work. There are a few ways to execute this important procedure which is made onto wood and steel form work.


- Fixing onto wood form work using nails.




- Fixing onto wood form work using staples.



- Fixing onto steel form work using pop rivets.




- Fixing onto steel form work using T bolts.



Removing The Strip Filler

Anchor channels are supplied with strip fillers within the open slot of the channels to prevent concrete ingress. This strip filler is removed as shown after the concrete is cured.




- Strip filler can easily be removed using a screw driver.

Connections To Channels

Fixtures are attached on to the anchor channels with T head bolts and lock nuts. There are suitable types for each Anchor channel section.

- Fixing T bolts into channels.




- Fixing lock nuts into channels.



Adjustability


T bolts are suitable to be inserted at the desired point along the length of the channel. Fixing is done by turning the T bolt 90 degrees clockwise and by tightening the nut. The correct torque values must be applied when tightening the nuts. T bolts must not be located beyond the last stud which is 25 mm from the end of the channel.



Unlocked



Locked




- Suitable T bolts can be inserted at desired point and adjusted easily along the length of the channel.
- To ensure correct installation of the T bolt the notch at the end of the shank must be checked.
- T bolts must not be positioned beyond the last stud on the channel.

HMPR-SP Special Types of Anchor Channels


Anchor Channels With Reinforcement Studs

Anchors can be manufactured out of reinforcement studs for special applications, particularly fixings in the edge of thin slabs. These channels have higher pull out loads and combined loads. Due to these qualities these channels are preferred for use in the fixing of curtain walls on to reinforced concrete beams.



Channels With Special Fabricated Elements

Special anchor channel manufacturing can be made according to the requirements of the project. Local testing as well as in house testing can be made to safely check the load capacities of the special anchor channels.




HMPR-SP Special Types of Anchor Channels

Curved Anchor Channels

Channels can be easily curved to an internal or external radius (lips inward or lips outward). Curves on elevation, such as brick arch details, which require special care, can be accommodated with these types of channels.

Inside Channel slot



Ri : Radius of inner channel

Outside channel slot



Ra : Radius of outer channel

Application :

- M & E works in Tunnels
- Installation on curved walls
- Connections to prefabricated pipes


Min. Radius	Channel Types								
	28/15	38/17	41/22	40/25	40/22	49/30	50/30	54/33	52/34
Inner channel - Ri	0.5 m	0.5 m	1.5 m	1 m	0.7 m	0.8 m	0.8 m	4 m	0.8 m
Outer channel - Ra	1.0 m	1.5 m	4 m	3 m	2 m	8 m	4 m	0.8 m	4 m

Channel Pair - Special Fabricated Unit

Where double or multiple fixings are required at known centres, channels can be welded to spacer straps, as shown below. The straps keep the channels parallel and accurately spaced along their length.

- Spacers are made either by steel strips or reinforced steel.

- Available in stainless steel and hot dip galvanized mild steel



Corner Fabricated Unit

Channels can be easily fabricated to suit corners, see below. (Smaller channels may be folded; larger channels are welded.)

- Standard leg dimensions are 125 mm by 250 mm. Other sizes can be produced upon request.

- Available in stainless steel and hot dip galvanized mild steel.



Channels With Strap Strip

If a narrow beam has a central reinforcement bar, anchors can be made to pass each side of the bar. This might occur where fixings for mechanical services are required in waffle slabs.



Channels With Wing Strip

Wing anchors are available for low profile details, e.g. where a channel is located in the concrete casing of a steel beam. The channel load capacity is reduced.




HMPR-MD Anchor Channels for Metal Deck Connections


The use of concrete cast on metal decking is being used more commonly in the building industry. Fixing of exterior facades such as curtain-walls, masonry walls, precast panels etc, are often required to be connected close to the edge of the metal deck. The metal deck anchor channels have good performance in thin slabs and in perimeter locations. The special designed assemblies made on the back of the channels provide strong bond with the concrete, when they are located within the reinforcement cage. Loads applied on the channel spreads over a longer area around the length of the slab edge. The workmanship of through deck fixing can be significantly reduced. The channels are easily placed before pouring the cement, with the channel studs or lugs of any suitable length to clear the ribs in the metal deck. Channels for metal decks are usually produced in hot dip galvanized mild steel. However, stainless steel grade 1.4301 and 1.4401 are also available upon request.




Special assembly made for connections on to edge of the slab. Channels are welded on to lugs that can have height distances to enable quick fixing on to the metal deck




Special assembly made for connection on to top of the slab. Assembly on skis with lugs that can be arranged to increase load performance and provide easy positioning on the metal deck




Connections made on the edge of the slab




Single Channel on skis assembly




Connections made on top of the slab



Channel pair on skis assembly



Channel pair assembly with toothed channels




HMPR-BL Anchor Channels for Balustrades

HMPR-BL anchor channels are the cold rolled channels with welded re bars. The **HMPR-BL** channels are used for fixing balustrades and hand rails on to the front faces of decks and balcony slabs. The re bars with stamped heads guarantee safe loading when fixing on thin slabs. The welded re bars are made out of ST500 build steel with ribs.

Advantages

- Fully adjustable
- Reduces significantly the construction time
- Permits adjustment and replacement of attached structures
- Can be used even on thin front faces of less than 100 mm
- T Head bolts are used instead of welding or anchor bolts




Technical Details

(Type 40/25, 49/30 & 54/33)



(Type 38/17)



Product Code	Length L (mm)	Stud Diameter Sd (mm)	Stud Length Sl (mm)	T Head Bolt Size	Product Code	Length La/Lb (mm)	Stud Diameter Sd (mm)	Stud Length Sl (mm)	T Head Bolt Size
HMPR-BL-38/17	100	10	201	M12x50 & M16x60	HMPR-BL-38/17	170 / 170	12	201	M12x50 & M16x60
	150								
	200								
HMPR-BL-40/25	100	10	90	M12x50 & M16x60	HMPR-BL-40/25	170 / 170	14	90	M12x50 & M16x60
	150								
	200								
HMPR-BL-49/30	100	12	110	M12x50 & M16x60	HMPR-BL-49/30	170 / 170	14	150	M12x50 & M16x60
	150								
	200								
HMPR-BL-54/33	100	14	200	M12x50 & M16x60	HMPR-BL-54/33	170 / 170	14	250	M12x50 & M16x60
	150								
	200								

Product Code

HMPR-BL - 38/17 - 100
 Length
 Section
 Type

Material:


A2: Stainless steel 1.4301,

A4 Stainless steel 1.4401,


HDG hot dip galvanized mild steel 1.0038 (S235JR)

(Studs are always out of steel BST 500S)

• Standard type



• Corner type




HAZ-TU Anchor Channels for Profiled Metal Sheeting - Introduction

HAZ-TU Anchor channels for profiled metal sheeting installation on reinforced concrete beams and columns are available in 3 and 6 mm thicknesses and 60/22 sections.


Fixing is done with self drilling screws or shot fired nails. Channels allow fast and economical installation as this system eliminates the difficult and time consuming anchor fixing into concrete.

Channels are inserted onto the surface of the concrete component flush to the surface and in the correct alignment. The end joints between channels should be minimum 20 mm. Fixing to the channels is made with either self drilling screws 6.3x22 or shot fired nails 4.5x24.


Channels are available in two standard types in 3 metre length with foam filling. Available materials are stainless steel grade 1.4301 (AISI 304) & 1.4401 (AISI 316) and hot dip galvanized mild steel.




- Fixing metal profiled sheets on to **HAZ-TU** anchor channels using self tabbing screws



- **HAZ-TU** anchor channels are casted in to concrete components




- Cladding material attached at the **EDGE** of the component




- Cladding material attached at the **TOP** of the component


HAZ-TU Anchor Channels for Profiled Metal Sheets - Product Details



HAZ-TU-C



HAZ-TU-B



HAZ-TU-A


HAZ-TU Cast in channels for profiles metal sheet installations are supplied in either 3 or 6 mm thicknesses. A foam filler is inserted in the open slot of the channel for preventing inflow of wet cement during casting. There are studs welded on to the channel for strong connections on to the concrete. There are three different stud versions which offer different results for loads and minimum edge spacings. Channels are supplied in Stainless steel and hot dip galvanized mild steel.




- The installation of profiled metal sheets on to prefabricated concrete components with embedded HPTR channels enables easy and economical fixing.




- Fixing is done with self drilling screws on to the HPTR cast in channels, without the need of pre-drilled holes. Power screw driver with 1500 rpm is required for fixing.




- HPTR channels are cast flush to the surface. The concrete surface should be trowelled smooth enabling the metal sheets to be positioned directly over the channels.



- Drilling positioning should be made in the middle of the channels, leaving a minimum distance $\frac{1}{3} w$ from the side of the channel.




- The minimum edge spacing (ae) should be no less than 20 mm. The distance (x) between the channel end and the screw position should be no less than 25 mm.



- The minimum spacing (ar) between channels should be 20 mm.

HAZ TU Anchor Channels - Technical Details


HAZ-TU-C



HAZ-TU-B



HAZ-TU-A




Product Code	Technical Details							Tensile - Max Design Load Bearing Capacity F_{ED} kN		
	Length	Channel Thickness	Section	Execution	No Of Studs	Stud Spacing	Stud Edge Distance	Single Loads	Pair Loads	Evenly distributed load
HAZ-TU 60/22/3-C2	3000	3	60/22	A	16	450	75	4.6	2.5	15.5
HAZ-TU 60/22/3-C3					40	150		7.0		46.6
HAZ-TU 60/22/6-C2	3000	6	60/22	B	16	450	75	7.0	2.5	15.5
HAZ-TU 60/22/6-C2					40	150		7.0		46.6
HAZ-TU 60/22/3-B2	3000	3	60/22	A	16	450	75	4.6	2.5	15.5
HAZ-TU 60/22/3-B3					40	150		7.0		46.6
HAZ-TU 60/22/6-B2	3000	6	60/22	B	16	450	75	7.0	2.5	15.5
HAZ-TU 60/22/6-B2					40	150		7.0		46.6
HAZ-TU 60/22/3-A2	3000	3	60/22	A	8	450	75	4.6	2.5	15.5
HAZ-TU 60/22/3-A3					20	150		7.0		46.6
HAZ-TU 60/22/6-A2	3000	6	60/22	B	8	450	75	7.0	2.5	15.5
HAZ-TU 60/22/6-A2					20	150		7.0		46.6

- Values are for concrete strength class C20/25
- Self drilled screws must be capable to support the indicated loads
- Set screws should be positioned in the central third of the channels width and no closer than 25 mm to channels end

Product Code

HAZ-TU-60/22/3-C2-3000




Type HAZ-TU C


Type HAZ-TU B

Type HAZ-TU A


Edge Distances (mm)						
a	ar	ae	af	d	b	
200	120	20	20	240	68	
200	100	20	20	200	75	
200	100	20	20	200	100	



Execution 2 : Can be cut into two pieces at the centre. Edge spacing must be minimum 75 mm.






Execution 3 : Can be cut into multiple pieces at the centre of two studs. Minimum edge space must be 75 mm.




HAZ-TU Self Locking Cast-in Channels - Product Details


HAZ TU type cast in channels are self locking channels for connections that are light weight. These channels are ideal for attachments of rails, metal cladding, window & door frames on to concrete substrate. Channels are available in pre-galvanized steel and hot dip galvanized steel.




HTU 40/25



HTU 60/25



HTU-80/25



Product Code	Technical Details									
	Dimensions			Loadings		Edge Spacings				
	Length (mm)	Thickness (mm)	Section (mm)	Safe load (kN)	Load Spacing (mm)	aa (mm)	ar (mm)	ae (mm)	af (mm)	d (mm)
HAZ-TU-40/25	3000	2.5	40/25	1.3	250	140	70	20	20	25
HAZ-TU-60/25	3000	2.5	60/25			160	80	20	20	25
HAZ-TU-80/25	3000	3.0	80/25			180	90	20	20	25.5

- Values are for concrete strength class C20/25
- Self drilled screws must be capable to support the indicated loads
- Load indicated is suitable for tensile, shear and resultant load

HPLS Anchor Plates - Product Details

HPLS Anchor plates is a product that offers solutions for attaching steel components to concrete substrates. anchor plates are cast in to the concrete with a flush surface. Corresponding steel or stainless steel elements are welded to the surface of the anchor plates. These elements are supplied in stainless steel and steel.

The allowable loads for the anchor plates for tensile, shear and bending moments are verified on project basis according to the required design criteria.

Anchor plates with 4 & 2 studs with flush surface suitable for welding



Anchor plates with 4 & 2 studs with tabbed holes suitable for attachments with screws



Anchor plates with 4 & 2 studs with welded threaded bars for attachments with hex nuts




Product Details			
Plate Sizes	Plate Thicknesses	Stud Diameters	Stud Lengths
70/100, 100/140, 160/160,	4, 6, 8, 10, 12	6	50
		8	50
		10	75
		12	100
		16	125

HWT Wall Ties - Introduction & Product Details


The **HWT** Wall ties provide secure and easy connections between concrete components. Serrated ties and washers enable safe transmittal of tensile loads.

Wall ties are used with cast in channels and T head bolts to achieve three dimensional adjustability for restraining attachments of prefabricated concrete components.

Wall ties are available in stainless steel 1.4301 & 1.4401 and hot dip galvanized W 1.0038 grade steel.



HWT - Wall Tie



Product Code	Projection + 20 (K mm)	Cavity + 20 (C mm)	Length (L mm)	Tensile Load all.F (kN)	Edge Distance (ar mm)	Slotted Hole (mm)
HWT - 28 -50	50	0	90	3.5	50	11x55
HWT - 28 -75	75	25	115			
HWT - 28 -100	100	50	140			
HWT - 28 -125	125	75	165			
HWT - 28 -150	150	100	190			
HWT - 28 -175	175	125	215			
HWT - 28 -200	200	150	240			

•To be used with HMPR-28/15 channels and HTB-28/15-M10x40 T Bolts.




HWT - 38 - 75	75	0	115	7.0	75	13x55
HWT - 38 - 100	100	25	140			
HWT - 38 - 125	125	50	165			
HWT - 38 - 150	150	75	190			
HWT - 38 - 175	175	100	215			
HWT - 38 - 200	200	125	240			

•To be used with HMPR-38/17 channels and HTB-38/17-M12x50 T Bolts.

HWT Wall Ties - Product Details

HWT-B Wall Tie




Product Code	Projection + 20 (K mm)	Cavity + 20 (C mm)	Length (L mm)	Tensile Load F (kN)	Edge Distance (ar mm)	Slotted Hole (mm)
HWT-B-28-75	75	25	115	3.5	50	11x55
HWT-B-28-100	100	50	140			
HWT-B-28-125	125	75	165			
HWT-B-28-150	150	100	190			
HWT-B-28-175	175	125	215			

•To be used with HMPR-28/15 channels and HTB-28 M10x40 T Bolts.

HWT-B-38-100	100	25	145	7.0	75	13x55
HWT-B-38-125	125	50	165			
HWT-B-38-150	150	75	195			
HWT-B-38-175	175	100	220			

•To be used with HMPR-38/17 channels and HTB-38 M12x50 T Bolts.

HWT-U Wall Tie



Product Code	Projection + 20 (K mm)	Cavity + 20 (C mm)	Length (L mm)	Tensile Load all. F(kN)	Edge Distance (ar mm)	Slotted Hole (mm)
HWT-U-38-200	200	125	245	7.0	75	13X60
HWT-U-38-225	225	150	270			
HWT-U-38-250	250	175	295			

•To be used with HMPR-38/17 channels and HTB-38 M12x50 T Bolts

HWT-U-49-200	200	50	245	12.0	150	17X60
HWT-U-49-225	225	75	270			
HWT-U-49-250	250	100	295			
HWT-U-49-275	275	125	320			
HWT-U-49-300	300	150	345			

•To be used with HMPR-49/30 channels and HTB-49 M16x60 T Bolts.

HWT-M Wall Ties for Masonry & MAS Brick Tie Channel Introduction


HWT-M Wall ties for masonry are used for the safe and easy connections of masonry blocks to the wall through connections made to cast in channels or surface fixed framing channels.

HWT-M type wall ties are designed for restraint attachments of both masonry wall facades and masonry walls to load bearing concrete walls. The sliding capability of the ties along the length of the channels decreases the risk of the masonry cracking due to structure movements.

The wall ties are inserted on the channel at desired points and are positioned by turning the ties 90 degrees clockwise. The perforated holes in the wall ties allow mortar filling to improve bonding.


Wall ties for masonry are available in stainless steel 1.4301 (AISI 304) & 1.4401 (AISI 316).

HWT-M Wall Tie



- Wall ties can be used for masonry wall connections fixed to load bearing walls. Embedding length (e) is achieved with the length of the wall tie.

- Wall ties can be used on masonry facade cladding. A minimum embedded length of 50 mm should be applied. The embedded length (e) is determined by correctly setting the length of the wall tie (L) and the masonry block width (d).




MAS-25/15 Brick tie channels are cold rolled pre-galvanized channels that have punched lugs on the back of the channels. This channel provides the same loading performance as the 28/15 and is an economic option for use in restraining brick walls on to concrete.


Lugs are punched out every 250 mm and the channels are supplied with a strip filler.

A debonding sleeve is used as a cover for the wall ties. This enables the wall tie to accommodate longitudinal movement in the direction of the tie. This is ideal when installing long masonry walls to concrete walls or when tying in large span infill walls to floor slabs. Debonding sleeves allow room for movement and prevents any cracking of the masonry walls.

**MAS-25/15
Brick Tie Channel**




- Lugs are prepunched on the back of the channel at 250 mm centres. The lugs are easily bent out on site prior to the casting of concrete.




- Wall ties are easily inserted into the debonding sleeves before installation is made.


HWT-M Wall Ties for Masonry - Product Details



• HWT wall ties can be used with cast in channels type 28/15 and 38/17.



• Connections on to surface fixed HMP channels type 28/15 and 38/17 can also be made.



• HMP channels can be welded on to structural steel to allow wall tie connections.

HWT-MS - Wall Tie



Product Code	Length (mm)	Thick-ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
HWT-MS 28 -125	125	1.25	25	28/15	2.5	1.4
HWT-MS 28 -185	185	1.25	25			
HWT-MS 28 -245	245	1.25	25			

HWT-MV - Wall Tie



Product Code	Length (mm)	Thick-ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
HWT-MV 28 - 85	85	2	26	28/15	3.2	2.7
HWT-MV 28 -120	120	2	26			
HWT-MV 28 -180	180	2	26			
HWT-MV 38 - 85	85	2	30	38/17	3.2	2.7
HWT-MV 38 -120	120	2	30			
HWT-MV 38 -180	180	2	30			

HWT-ML - Wall Tie



Product Code	Length (mm)	Thick-ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
HWT-ML 28 - 85	85	3	25	28/15	3.2	2.7
HWT-ML 28 -120	120	3	25			
HWT-ML 28 -180	180	3	25			
HWT-ML 38 - 85	85	3	30	38/17	3.2	2.7
HWT-ML 38 -120	120	3	30			
HWT-ML 38 -180	180	3	30			

HWT-MT - Wall Tie





Product Code	Length (mm)	Thick-ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
HWT-MT 28 - 85	85	3	25	18/15	3.2	2.7
HWT-MT 28 -120	120	3	25			
HWT-MT 28 -180	180	3	25			
HWT-MT 38 - 85	85	3	30	38/17	3.2	2.7
HWT-MT 38 -120	120	3	30			
HWT-MT 38 -180	180	3	30			


HTB T Bolts & HMLN Lock Nuts - Introduction

HTB T bolts & HMLN lock nuts for attachment in to cast in channels are specially designed for a perfect fit into the section of the channels. Insertion is made and after a 90 degree turn clockwise the fixing is made. Correct torque values must be applied in order to achieve secure connections.

T bolts and lock nuts are available in stainless steel 1.4401 and hot dip galvanised steel strength class 4.6 & 8.8.



Fixing Instructions



1.) After pouring of cement, the concrete wall should be left to dry



2.) After concrete has dried out, the filler in the channel should be taken out using a suitable tool



3.) The filler can be pulled out along the length of the channel simply by hand



4.) No filler or concrete left overs should be left within the channel slot. Any residue should be scrapped out



5.) Suitable T head bolts should be inserted into place by placing the narrow side of the head in the slot



6.) Locking in place will be done when turning 90 degrees. Notch on the shank must be set vertically



7.) T head bolts can be adjusted along the length of the channel to be in the desired position




8.) When the connection has been made recommended torque must be used in order to fasten the T bolts

HTB T Bolts & HMLN Lock Nuts - Technical Details

T head Bolt Metric Size	Loading Table for T Head Bolts (kN)													Max Torque Loads (Nm)			
	Grade	4.6 Class Steel			8.8 Class Steel			Stainless Steel 1.4401 /A4-50			Stainless Steel 1.4401 /A4-70			4.6 Class Steel	8.8 Class Steel	1.4401 / A4-50	1.4401 / A4-70
	Loads	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load				
M6	all.F	2.2	2.0	0.10	-	-	-	2.2	1.8	0.1	3.0	3.8	0.1	3	-	3	4
	F Rd	3.1	2.8	0.14	-	-	-	3.1	2.5	0.1	4.2	5.3	0.2				
M8	all.F	4.0	5.0	0.20	-	-	-	4.0	4.4	0.2	5.5	9.4	0.3	8	-	8	10
	F Rd	5.6	7.0	0.28	-	-	-	5.6	6.2	0.3	7.7	13.2	0.4				
M10	all.F	6.4	10.0	0.30	13.3	24.9	1.1	6.4	8.7	0.3	8.7	18.7	0.4	15	48	15	20
	F Rd	9.0	14.0	0.42	18.6	34.9	1.5	9.0	12.2	0.4	12.2	26.2	0.6				
M12	all.F	9.3	17.5	0.50	19.4	43.7	1.6	9.3	15.3	0.5	12.6	32.8	0.7	25	70	25	35
	F Rd	13.0	24.5	0.70	27.2	61.2	2.2	13.0	21.4	0.7	17.6	45.9	1.0				
M16	all.F	17.3	44.4	0.90	36.1	110.0	3.0	17.3	38.8	0.9	23.6	83.3	1.2	60	200	60	80
	F Rd	24.2	62.2	1.26	50.5	154.0	4.2	24.2	54.3	1.3	33.0	116.6	1.7				
M20	all.F	27.0	86.5	1.40	56.4	216.4	4.7	27.0	75.7	1.4	36.8	162.3	1.9	120	400	120	160
	F Rd	37.8	121.1	1.96	79.0	303.0	6.6	37.8	106.0	2.0	51.5	227.2	2.6				
M24	all.F	38.8	149.9	2.00	81.2	-	-	38.8	130.9	2.0	-	-	-	200	680	200	-
	F Rd	54.3	209.9	2.80	113.7	-	-	54.3	183.3	2.8	-	-	-				
M30	all.F	61.7	299.9	3.20	129.0	-	-	61.7	262.4	3.2	-	-	-	400	1.400	400	-
	F Rd	86.4	419.9	4.48	180.6	-	-	86.4	367.4	4.5	-	-	-				

Loading Table For Locknuts (kN)																					
Lock Nut Type		HMLN-28			HMLN-38			HMLN-41				HMLN-40			HMLN-50			HMLN-72			
		M6	M8	M10	M8	M10	M12	M6	M8	M10	M12	M8	M10	M12	M10	M12	M16	M12	M16	M20	
Safe	all.F	1.9	2.8	3.0	4.0	4.1	5.7	4.0	4.0	6.4	9.3	4.0	6.4	9.3	6.4	9.3	9.3	9.3	17.3	22.0	
Load	F _{Rd}	2.7	3.9	4.2	5.6	5.7	8.0	5.6	5.6	9.0	13.0	5.6	9.0	13.0	9.0	13.0	13.0	13.0	24.2	30.8	

Metric Size	Longitudinal Loading On Toothed Channel				
	Grade	Mild Steel		Stainless Steel	
	Loads	Longitudinal Load	Max Torque (Nm)	Tensile & Shear	Longitudinal Load
M8	all.F	4.0	28.0	4.0	16.0
M10	all.F	5.0	55.0	5.0	31.5
M12	all.F	5.0	75.0	5.0	55.0
M16	all.F	7.5	125.0	5.0	125.0




- The length of the T bolt must be determined using the formula below


$$(L_{\text{erf}} = t_{\text{fix}} + i + s + v)$$

Dimensions V min


Metric	Vmin (mm)
M6	11.0
M8	12.5
M10	14.5
M12	17.0
M16	20.5
M20	26.0
M24	29.0
M27	31.5
M30	33.5




- Square washers must always be used in cases of installations with spacings.




- Installations must always be made flush to the surface. Contact must be established between the fixture and the cast in channel.




- In cases of non flush surfaces, a square washer and a shim must be used to enable secure transfer of loads on to the channels.




HTB T Bolts - Product Details

Product Code	Technical Details							Product Drawing
	Bolt Size mm	Metric M (mm)	Length L (mm)	Head Thick a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for Channels	
HTB-28-8/30	M8x30	8	30	4.0	10.50	23.0	HMPR-28/15	
HTB-28-8/50	M8x50	8	50					
HTB-28-10/40	M10x40	10	40					
HTB-28-10/60	M10x60	10	60					
HTB-38-10/40	M10x40	10	40	7.0	13.00	30.5	HMPR-38/17	
HTB-38-10/50	M10x50	10	50					
HTB-38-10/70	M10x70	10	70					
HTB-38-12/50	M12x50	12	50					
HTB-38-12/60	M12x60	12	60					
HTB-38-12/80	M12x80	12	80					
HTB-38-16/80	M16x60	16	60					
HTB-38-16/80	M16x80	16	80					
HTB-38-16/100	M16x100	16	100					

• HTB T bolts are stamped with HAZ or HS trademark

Product Code	Technical Details							Product Drawing
	Bolt Size mm	Metric M (mm)	Length L (mm)	Head thick a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for Channels	
HTB-40-10/50	M10x50	10	50	12.0	14.00	34.0	HMPR-40/25, HMPR-H-40/22	
HTB-40-10/70	M10x70	10	70					
HTB-40-12/50	M12x50	12	50					
HTB-40-12/60	M12x60	12	60					
HTB-40-12/80	M12x80	12	80					
HTB-40-16/80	M16x60	16	60					
HTB-40-16/80	M16x80	16	80					
HTB-40-16/100	M16x100	16	100					
HTB-50-12/50	M12x50	12	50	13.0	17.50	42.0	HMPR-49/30, HMPR-54/33, HMPR-H-50/30, HMPR-H-52/34	
HTB-50-12/60	M12x60	12	60					
HTB-50-12/80	M12x80	12	80					
HTB-50-16/60	M16x60	16	60					
HTB-50-16/80	M16x80	16	80					
HTB-50-16/100	M16x100	16	100					
HTB-50-20/80	M20x80	20	80					
HTB-50-20/100	M20x100	20	100					
HTB-72-20/60	M20x60	20	60	17.0	22.00	58.0	HMPR-72/49	
HTB-72-20/80	M20x80	20	80					
HTB-72-20/100	M20x100	20	100					
HTB-72-24/80	M24x80	24	80					
HTB-72-24/100	M24x100	24	100					

• HTB T bolts are stamped with HAZ or HS trademark

Product Code	Technical Details							Product Drawing
	Bolt Size mm	Metric M (mm)	Length L (mm)	Head Thick a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for Channels	
HTB-41-12/50	M12x50	12	50	10.0	20.00	34.0	HMPR-S-41/22	
HTB-41-16/60	M16x60	16	60					

• HTB T bolts are stamped with HAZ or HS trademark

Product Code

HTB - 28 - 8 / 30


— Metric / Length
— Channel type
— Type

• Material:


A4 Stainless steel 1.4401,


HDG 4.6 hot dip galvanized steel strenght class 4.6


HDG 8.8 hot dip galvanized steel strenght class 8.8



HMLN Lock Nuts - Product Details

Product Code	Technical Details					Product Drawing
	Metric Size M (mm)	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for Channels	
HMLN-28-6	6	4.0	13.00	24.5	HMPR-28/15	
HMLN-28-8	8					
HMLN-28-10	10					
HMLN-38-10	10	6.0	17.50	31.5	HMPR-38/17	
HMLN-38-12	10					
HMLN-38-16	10					

Product Code	Technical Details					Product Drawing
	Metric Size M (mm)	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for Channels	
HMLN-40-10	10	10.8	17.00	34.5	HMPR-40/25, HMPR-H-40/22	
HMLN-40-12	12					
HMLN-40-16	16					
HMLN-50-10	10	11.7	21.0	43.5	HMPR-49/30, HMPR-54/33, HMPR-H-50/30, HMPR-H-52/34	
HMLN-50-12	12					
HMLN-50-16	16					
HMLN-72-12	12	22.0	31.00	62.0	HMPR-72/49	
HMLN-72-16	16					
HMLN-72-20	20					

Product code	Technical details					Product drawing
	Bolt size mm	Head thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for channels	
HMLN-41-6	6	6.0	20.00	34.0	HMPR-S-41/22	 
HMLN-41-8	8	8.0				
HMLN-41-10	10	10.0				
HMLN-41-12	12	12.0				

Product Code	Technical Details					Product Drawing
	Bolt Size mm	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Suitable for Channels	
HMLN-S-41-6	6	6.0	20.00	34.0	HMPR-S-41/22	
HMLN-S-41-8	8	8.0				
HMLN-S-41-10	10	10.0				
HMLN-S-41-12	12	12.0				

Product Code

HMLN - 28 - 6

— Metric
— Channel type
— Type

• Material:


A4 Stainless steel W 1.4401,
HDG hot dip galvanized steel

HMPR Anchor Channels - Application Examples

HMPR Anchor channels with studs and corresponding T head bolts for are used for strong and secure connections in to concrete without the use of drilling. Suitable for connections of any type of secondary structures. Loads up to 27.0 kN are applicable .

Advantages:


- No drilling on site.
- No noise and vibration of power tools.
- Safe near edges on concrete.
- Adjustable and flexible.
- Safe and secure fixing.
- Quick and easy fixing.
- Applicable for all type installations.



• Installation of curtain walls

• Installation of natural stone panels

• Installation of masonry walls



• Installation of precast concrete panels

• Connection of concrete beams

• Installation of pipe systems


HMPR Anchor Channels - Application Examples




• Installation of base components




• Installation of stadium seats




• Installation of pipe systems



• Wall connections




• Wall connections



• Upper beam connection



• Base connection



• Lower beam connection

HFB Facade Brackets

Curtain wall facades are used more frequently in the external facade cladding for modern buildings. The curtain wall technology is the most advanced type of facade construction which are preferred because of its aesthetics and functionality. This type of cladding also offers high thermal and load performance and can be installed faster and easier than any other conventional type of claddings.

HAZ Metal designs and manufactures facade brackets for the installation of curtain wall panels on to the structure. **HFB** facade support brackets are used to fix longitudinal and transverse curtain wall systems. The brackets transfer the acting loads in to the structure. These brackets can be designed to adapt to any type of application with accordance to the design criteria.

HFB facade brackets are designed and dimensioned to with stand high horizontal and vertical loads. The facade brackets are available in two main categories.

The first category of facade brackets are the ones that can be fixed on the edge of the slabs. This way the tensile loads from wind are transferred in to the end of the floor slab.

The second category of facade brackets are the ones that are fixed on the top of the slab. This way the horizontal loads from wind and the vertical loads from dead load and the resultant loads are transferred in to the top of the floor slab.

The facade brackets offer great advantages when used with **HMPR** anchor channels. Both secure and easy connections are enables with the verified load performance values and the high adjustability properties of the **HMPR** anchor channels.

Advantages

- Simple and fast installation due to the adjustability of the system in all directions
- Smaller edge distances make it possible to fix close to the edge or front end of the floor slabs
- High load performance both for horizontal and vertical loads. Up to 32 kN loads possible
- Can be specially designed and dimensioned to suit various type of fixing applications



• Modern high rise buildings



• Curtain wall fixing at the edge of floor slab



• Curtain wall fixing at the edge of floor slab

HFB Facade Support Brackets - Product Range

Application details

- Bracket for installing curtain wall at top of slabs

- Quick and Easy Installation with hang on method

- ± 10 mm vertical adjustment through incorporated set screws on the bracket

- In and out adjustability through the slotted holes. Fixing at desired point is made with serrated washers

- Lateral adjustability made with on the cast in channel. Fixing is made with two T head bolts

- Can be designed to take wind loads of up to 24 kN

- Can be designed to take dead loads of up to 7 kN

- Available in stainless steel and hot dip galvanized mild steel


HFB-LH Facade Support Bracket



HFB-AP Facade Support Bracket



HFB-MT Facade Support Bracket



Application details


- Brackets for installing curtain walls at edge of slabs

- Adjustability made through slot holes. Position fixing is made with serrated washers

- Easy fixing with uncomplicated parts

- Available in stainless steel and galvanized steel

HFB-MT Facade Support Bracket



HFB-MT Facade Support Bracket



HAZ-RBX Recess Box Anchor Channels

Unitized curtain systems are often installed at the top of the slab. This creates a problem in which the brackets used to install the curtain wall panels stand out above the finishing line of the floor.

As a result, usable area is reduced and aesthetics is compromised. The use of the HAZ-RBX Recess Box anchor channels, provide a solution for this problem.

The HAZ -RBX anchor channels are supplied with the suitable anchor channel which creates a void in the concrete that allows the bracket to be installed below the finished floor level.

The HAZ-RBX channel is an assembled box made out of galvanized steel or epoxy paint coated steel recess box, that is tack welded with a suitable anchor channel. The type and size of the anchor channel is determined according to the design loads of the curtain wall application.

The box is filled with foam to avoid access of concrete in to the void. There are nail holes on the steel box to allow secure connection of the box on to wooden form work.

After the installation of the HAZ-RBX anchor channels on to the form work is completed, concrete is poured leaving the top of the box flush with the concrete pour.

Once the concrete is dried, the foam filler is pulled out and the void is exposed. The curtain wall support bracket is installed on to the anchor channels using t head bolts.


After the installation is finished and the support bracket is tightened, the void is filled with concrete or grout. The bracket is covered and the void is completely filled leaving a flush finished floor.

Features and benefits:

- The HAZ-BRX Recess box channel is manufactured with tight tolerances
- Dimensions can be customized to application requirements
- Nail holes are available for fixing the box to wooden form work
- Foam filler is provided with an exact fit to avoid concrete ingress
- Anchor channels are tack welded to the recess box
- Corrosion resistant epoxy paint coating or hot dip galvanizing made to the recess box




- HAZ-RBX Recess Box Anchor channels can be supplied with any type of anchor channels



- HAZ-RBX Recess Box Anchor channels are supplied with foam filling to avoid concrete recess in to the void



- HAZ-RBX Recess Box Anchor channels are used for curtain wall installation at the top of the slab



- HAZ-RBX Recess Box Anchor channels can be custom made. The above dimensions (mm) are for HMPR -CE- 49/30-350 type channel

Anchor Channels Application Pictures

Anchor channels are in all kind of connections in to concrete. All types of facade applications can be executed using anchor channels. This is preferred due to its easy and fast installation. Below are pictures taken from anchor channels applications used in the wide construction applications.



Stone cladding on secondary structure fixed on anchor channels



Curtain wall cladding fixed on anchor channels on the edge of slab



Brick work cladding fixed on anchor anchor channels

Curtain wall cladding fixed on anchor channels on the top of slab



Various anchor channel applications used on areas such as, electric utility, water management and in tunnels



Stadium seating fixed on anchor channels



References



Infinity Tower, Brisbane



Adnoc HQ, Abu Dhabi



Renesance Tower, Istanbul



The Ruby Tower, Mumbai



Telekom HQ, Ankara



Dolphin Tower, Ankara



Ciftci Towers, Istanbul



Emaar Square, Istanbul



Centre for Technology and Design, St Polten

References



Ang Mo Kio ITE Headquarters, Singapore



Hyflux Innovation Centre, Singapore



Conrad Hotel, Dubai



Ritz Carlton Hotel, Kuala Lumpur



Rasuna Tower, Jakarta



Orchard Emerald, Singapore



Dorsett Hotel, Singapore

References



Infinity Tower, Brisbane



Adnoc HQ, Abu Dhabi



Renesance Tower, Istanbul



The Ruby Tower, Mumbai



Telekom HQ, Ankara



Dolphin Tower, Ankara



Ciftci Towers, Istanbul



Emaar Square, Istanbul



Awly Building, Christchurch

References



Ang Mo Kio ITE Headquarters, Singapore



Hyflux Innovation Centre, Singapore



Conrad Hotel, Dubai



Awly Building, Christchurch



Orchard Emerald, Singapore



Dorsett Hotel, Singapore



HAZ PAZARLAMA İÇ & DIŞ TİC. A.Ş.
Sarıkanyar Sok. Ece Apt. No. 8/1
Kozyatağı Mah. 34742 Kadıköy
İstanbul, TÜRKİYE
Tel : +90 (0) 216 410 72 26
Fax : +90 (0) 216 410 71 41
www.hazpazarlama.com
hazpazarlama@hazgrp.com

HAZ INTERNATIONAL LTD.
154 Great North Road Hatfield
Herts. AL9 5JN England
Tel : +44 (0) 1707 - 260 180
Fax : +44 (0) 1707 - 260 190
www.hazuk.co.uk
haz@hazuk.co.uk

HAZ EGYPT LTD
Villa no.29-Third Floor.St.no.270
New Maadi, Cairo, Egypt
Tel : +20 (2) 27038223
Fax : +20 (2) 27038223
www.hazeg.com
info@hazeg.com

HAZ METAL SANAYİ VE TİCARET A.Ş.
Şehit Er Çıracı Caddesi No. 10
Akçay Sanayi Bölgesi 31200 İskenderun
Hatay, TÜRKİYE
Tel : +90 (0) 326 626 20 50
Fax : +90 (0) 326 626 20 45
www.hazmetal.com
info@hazmetal.com

HAZ MARBLE INDUSTRY & TRADE LLC
First Gulf Building Corniche Street
2nd Floor, Flat No. 202 P.O. Box 5721
Abu Dhabi, United Arab Emirates
Tel : +971 (0) 2 622 07 00
Fax : +971 (0) 2 622 17 00
www.hazuae.ae
hazuae@hazmarbleuae.ae

HAZ MARBLE QATAR WLL
P.O.BOX 31296 C-Ring road
Doha, Qatar
Tel : +974 (0) 467 26 49
Fax : +974 (0) 467 47 49
www.hazqatar.com
hazdoha@hazqatar.com

HAZ METAL DEUTSCHLAND GmbH
Leonhard Karl Strasse 29
97877 Wertheim, Germany
Tel : +49 (0) 9342 93590
Fax : +49 (0) 9342 935929
www.hazmetal.de
info@hazmetal.de

HAZ ASIA PACIFIC PTE LTD
Blk 22 Woodlands Link #01-65
Singapore 738734
Tel: +65 6853 7681
Fax: +65 6752 9582
www.hazapac.com
info@hazapac.com

HAZ RUS LTD
117036, Ul, Profsoyuznaya Dom 3 (office 531)
Moscow, Russian Federation
Tel : +7 (495) 781 39 95
: +7 (926) 672 31 84
info@hazrus.ru
www.hazrus.ru



Always at the forefront of fixing technology, HAZ METAL has earned a reputation as the leaders in fixing systems innovation and is regarded as the one to follow. HAZ METAL fixing systems of today become the standard of tomorrow.

HAZ METAL combines the very latest international technology with its own research and development team to establish a technical excellence within the industry. HAZ METAL readily embraces the responsibility of a major producer and shares its expertise with problem solving solutions.